

Power		
Power Source	Electric	Gas
Engine	N/A	Kawasaki 351 cc
Drive Motor	48-volt	N/A
Horsepower	3.2 (continuous)/10 (intermittent)	11.5 @ 3,600 rpm , exceeds SAE J1940 Performance Standards.
Governor	Automatic, ground speed sensing, internally geared-in unitized transaxle	Automatic, ground speed sensing, internally geared-in unitized transaxle

Agility		
Power Source	Electric	Gas
Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
Suspension - Front	Independent leaf springs w/dual hydraulic shocks	Independent leaf springs w/dual hydraulic shocks
suspension - Rear	Leaf springs w/dual hydraulic shocks	Leaf springs w/dual hydraulic shocks
Brakes	Rear-wheel, mechanical drum	Rear-wheel, mechanical drum
Park Brake	Foot-operated	Foot-operated

Strength / Design		
Power Source	Electric	Gas
Frame Chasis	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame	Rust-proof non-corrosive, aircraft-grade 6061 aluminum frame
Body - Front	ABS plastic	ABS plastic
Body - Rear	ArmorFlex®	ArmorFlex®
Tires - Front	20 x 10.00-8, 4-ply rated, All-trail II	20 x 10.00-8, 4-ply rated, All-trail II
Tires - Rear	20 x 10.00-8, 4-ply rated, All-trail II	20 x 10.00-8, 4-ply rated, All-trail II
Cargo Box Size	27.5 x 43.5 x 11 in (65.3 x 110.5 x 27.9 cm)	27.5 x 43.5 x 11 in (65.3 x 110.5 x 27.9 cm)
Bed Capacity	300 lb (136.1 kg)	300 lb (136.1 kg)

Total Vehicle Capacity	800 lb (363.2 kg)	800 lb (363.2 kg)
Overall Length	101 in (256.6 cm)	101 in (256.6 cm)
Overall Width	53 in (134.6 cm)	53 in (134.6 cm)
Overall Height	48.0 in (121.9 cm)	48.0 in (121.9 cm)
Wheelbase	65 in (165.1 cm)	65 in (165.1 cm)
Ground Clearance	5.5 in (14 cm)	5.5 in (14 cm)
Fuel Tank Capacity	N/A	7 gal (26.5L)
Tread (Front/Rear)	34 in front / 38 in rear (86.4 cm/96.5 cm)	34 in front / 38 in rear (86.4 cm/96.5 cm)
Dry Weight Less Batteries	889 lb (403.2 kg)	805 lb (365.1 kg)
Maximum Speed	17-19 mph	17-19 mph
Turning Radius	8.75 ft (2.7 m)	8.75 ft (2.7 m)
Vehicle Warranty	2-year/2000-hour limited	2-year/2000-hour limited